

# ProClean

---

# GROUT AID

FINAL RINSE ADDITIVE



## ProClean GROUT AID

FINAL RINSE ADDITIVE

- Final rinse additive for easy wash-down
- Helps eliminate Grout Haze
- Suitable for use with Natural Stone, Ceramic & Porcelain Tiles
- Simply add to clean water



1L e



suitable for internal  
and external use

1L

## Product Selection Guide

### Suitable surface & substrates:

✓	Sandstone	✓	Terracotta
✓	Porcelain	✓	Quarry Tile
✓	Slate	✓	Granite
✓	Ceramic	✓	Non acid-sensitive tiled surfaces

**ULTRA**<sup>®</sup>  
**TILE**

# TECHNICAL DATASHEET

## DESCRIPTION

- Use indoors and outdoors during the installation process
- Suitable for all acid resistant surfaces
- Use on ceramic tiles, porcelain, brick, clay and quarry tiles, terracotta, concrete and other types of natural stone
- Internal & external use

UltraTile Grout Aid is a final rinse additive aiding easy rinse and clean off of mortar grout and cement grouting residues. It helps to eliminate common problematic grout film and hazing.

Grout Aid Plus significantly reduces grout haze drying on the surface; this will greatly reduce post installation problems such as patchy grout colours and efflorescence blooming. Grout Aid will only neutralise cement grout residues it is not designed to remove grout polymer film issues. To deal with those issues we would recommend using UltraTile Resin-Off.

**Grout Aid Plus is not suitable for use with or around acid sensitive surfaces such as enamel, zinc, chrome, stainless steel, polished marble and limestone, etc.**

## DIRECTIONS FOR USE

- 1) Always perform a test in an inconspicuous area on-site to check suitability of product, prior to use - read these instructions fully before application. If you experience difficulties using this product, please contact our technical support team on the number above.**
- 2) Always use rubber or latex gloves when using this product.
- 3) Add 100-200ml per 5 litres of final rinsing water in a bucket. Mix well. Proceed to use as normal with a grouting sponge or tiler's washboy to clean.
- 4) Allow to dry (2-5mins). On rough or textured tiles, it may be necessary for a second wash down.
- 5) If using Grout Aid indoors ensure good ventilation during and after use.

## COVERAGE

Up to 100m<sup>2</sup> per litre

Coverage will vary depending on surface contamination and dilution rate used.

## POINTS OF NOTE

Please ensure that appropriate PPE is used when using this product. Depending on surface texture, structure and porosity a higher dilution with more Grout Aid liquid may be required. Not to be used for general purpose cleaning. Always protect these areas. Always test this product in an inconspicuous area. It remains the responsibility of the end user to check the suitability of the product.

## STORAGE

This product must be stored in unopened bottles, in a frost free environment out of direct sunlight. Avoid frost. Ideal storage temperatures are between 5°C and 25°C.

## SHELF LIFE

Under the above storage conditions this product has a shelf life of 12 months from production date.

### Precautions:

H314: Causes severe skin burns and eye damage. H290: May be corrosive to metals. H302: Harmful if swallowed. 302+312+332: Harmful if swallowed, in contact with skin or if inhaled. H315: Causes skin irritation. H317: May cause an allergic skin reaction. H318: Causes serious eye damage. H335: May cause respiratory irritation. P264: Wash hands thoroughly after handling. P280: Wear eye protection. P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P301+330+331: IF SWALLOWED: rinse mouth. Do NOT induce vomiting. P302+350: IF ON SKIN: Gently wash with plenty of soap and water. P304+341: IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. P333+313: If skin irritation or rash occurs: Get medical advice/attention. P337+313: If eye irritation persists: Get medical advice/attention.



## HEALTH & SAFETY

Please ensure that appropriate PPE is used when preparing, mixing and applying products. Always wash hands before consuming food and make sure that materials are kept safely out of reach of children and animals. Please dispose of packaging and waste appropriately. A full Material Safety Data Sheet relating to this product is available to download online.



Read this guide in full. Always complete a test application before proceeding.  
If you have any questions please contact our technical support team on 01827 254402.

Instarmac Group plc  
Danny Morson Way, Birch Coppice Business Park  
Dordon, Tamworth, Staffordshire B78 1SE  
t: +44 (0)1827 254402  
e: enquiries@instarmac.co.uk orders: orders@instarmac.co.uk

w: instarmac.co.uk

Vers 01.10.2022 Information correct at time of print. Uncontrolled if printed. For the most up-to-date version of this datasheet, please refer to this product's profile on our website which can be found at [www.ultratileadhesives.co.uk](http://www.ultratileadhesives.co.uk)



# TECHNICAL DATASHEET

## QUALITY ASSURANCE

All products are manufactured in a plant whose quality management system is certified as being in conformity with BE EN ISO 9001. Products are guaranteed against defective materials and manufacture and will be replaced or money refunded if the goods do not comply with our promotional literature. We cannot however accept responsibility arising from the application or use of our products because we have no direct or continuous control over where and how our products are used. All UltraTile products are sold subject to our terms and conditions of sales, copies of which may be obtained upon request.

## TECHNICAL DATA

Unit Size:	1L Bottle
Colour:	Yellow
Application Temperatures:	5°C to 25°C
ph Value:	1-2

## USAGE GUIDELINES

Dwell Time Guidance:	2-5 minutes*
Applications / Coats:	1-2 applications
Application Method:	Sponge / Cloth
Dilution:	Varies, see directions for use

\*Depending on temperatures, substrate and site conditions.



Read this guide in full. Always complete a test application before proceeding.  
If you have any questions please contact our technical support team on 01827 254402.

Instarmac Group plc  
Danny Morson Way, Birch Coppice Business Park  
Dordon, Tamworth, Staffordshire B78 1SE  
t: +44 (0)1827 254402  
e: enquiries@instarmac.co.uk orders: orders@instarmac.co.uk  
w: instarmac.co.uk

Vers 01.10.2022 Information correct at time of print. Uncontrolled if printed. For the most up-to-date version of this datasheet, please refer to this product's profile on our website which can be found at [www.ultratileadhesives.co.uk](http://www.ultratileadhesives.co.uk)

